

# DATA SHEET

## A17-3

Issue: May 2009

### All-round Display

### A Line TFT 43 cm/17-inch display – Enter the world of LCD

The A17-3 offers you all the benefits of the LCD technology at a very competitive price.

**Excellent visual ergonomics for the office with 1280 x 1024 recommended resolution, 800:1 typical contrast and excellent brightness of 300 cd/m<sup>2</sup>**

**Fast response time (typ.) of 5 ms, perfect for Internet, office multitasking and more**

**Proven eco friendliness with TCO'03 and Energy Star**

**Representative design providing a slender housing in ergonomic light grey, integrated speakers and power supply**



## A17-3

### Ergonomic stand

Tilt angle -5° / + 20°

### Picture performance

Contrast - typical 800:1

Response time  
typical 5 ms

Viewing angle (h/v) 170° / 170°

Brightness - typical 300 cd/m<sup>2</sup>

### Size and resolution

Aspect ratio 5:4

Diagonal Size 43 cm / 17-inch

Resolution (native) 1280 x 1024 pixel (recommended)

Resolution  
(interpolated) 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel

Picture size 338 x 270 mm

Pixel Pitch 0.264 mm

### Frequencies

Horizontal 30 - 82 kHz

Vertical 55 - 75 Hz

### Connectivity

Video input 1 x D-SUB

Audio sound output 2 x 1 W

Audio signal input 3.5 mm stereo phone jack

### Ease-of-use menu

Languages Dutch, English, French, German, Italian, Russian, Spanish, Swedish

Brightness /  
Contrast Brightness, Contrast, Black level, Auto level

Color sRGB, 6500K, 9300K, Native, Custom Color (R,G,B)

Image adjust Clock, Phase, H-Position, V-Position

Audio Mute, Volume

Information Model name, S/N, Resolution/mode

Setup Language, DDC-CI, OSD-Position, OSD-Timeout, Factory recall

### Power consumption

Soft switch off 0.6 W

Power save mode 0.7 W

Operating with EPA  
settings 22 W

Operating maximum  
brightness 35 W

### Electrical values

Rated voltage range 100 - 240 V

Rated frequency  
range 50 - 60 Hz

Protection class 1

### Compliance

Germany GS

Europe CE

USA/Canada FCC Class B, cUL

Russia GOST

China CCC

Saudi Arabia SASO

Global TCO'03, ENERGY STAR® 4.1, ISO13406-2 (Pixel fault class II), IT-Eco-Declaration, RoHS, WEEE

Compliance link <https://sp.ts.fujitsu.com/sites/certificates/default.aspx>

---

**Quality and Reliability**

MTBF (demonstrated) 70000 h

---

**Dimensions / Weight / Environmental**

Dimension without stand (W x D x H) 373 x 62 x 322

Dimension with stand (W x D x H) 373 x 200 x 377

Weight (packed) 5.8

Weight (unpacked) 3.9 kg

Weight (Monitor only)

Operating ambient temperature 5 - 35°C

---

**Miscellaneous**

Kensington lock prepared

---

**Package content**

D-SUB Data cable 1.8m , Audio cable , Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, Quickstart flyer, Warranty booklet, Safety booklet

Data cables and audio cable detachable on display

---

**Order information**

Order Code S26361-K1146-V140

EAN-Nr. 4049699076404

---

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:

<http://ts.fujitsu.com/aboutus>

Take back and Recycling information:

<http://ts.fujitsu.com/recycling>

---

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Published by Fujitsu Technology Solutions <http://ts.fujitsu.com>

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)

Copyright © Fujitsu Technology Solutions May 2009